

NBH

Moulded Case Circuit Breaker



NBH-100



NBH-250



NBH-400

Application

Type			NBH-50	NBH-60	NBH-100	NBH-250	NBH-400
Pole	2P		NBH52c	NBH62c	NBH102c	NBH202c	NBH402c
	3P		NBH53c	NBH63c	NBH103c	NBH203c	NBH403c
	4P		NBH54c	NBH64c	NBH104c	NBH204c	NBH403c
Rated current In A			15,20,30,40,50	15,20,30,40,50,60	15,20,30,40,50,60,75,100	100,125,150,175,200,225,250	250,300,350,400
Rated operational voltage,Ue	AC(V)		690	690	690	690	690
	DC(V)		500	500	500	500	500
Rated insulation voltage Ui (V)			750	750	750	750	750
Rated impulse withstand voltage Uimp			8	8	8	8	8
Rated short-circuit breaking capacity(Icu)	AC	690V	2.5	2.5	5	8	5
		480/500V	7.5	7.5	10	18	18
		415/460V	14	14	18	26	37
		380V	18	18	22	30	42
		220/250V	30	30	35	65	50
	DC	500V(3P)	5	5	10	10	10
		250(2P)	5	5	10	10	10
Ics=%Icu			100	100	100	100	100
Dimensions WxHxD			75x130x60mm	75x130x60mm	75x130x60mm	105x165x60mm	140x257x109mm